

Boston

Horizon HS 40, 50, 60, 225
Bookshelf and LCR Speakers

play in color. play smart.



Color changes everything
HS 40 models shown

Three small footprint choices for bookshelves, side tables, and desktops, plus a dual-woofer LCR speaker that will complement any video monitor (especially the flat ones). With soft-dome tweeters and midrange drivers, Horizon compact speakers deliver surprising performance at a reasonable price.

Boston

Horizon HS 40, 50, 60, 225
Bookshelf and LCR Speakers



HS 225
mist and midnight

Make it your own with the Boston Personal Options Plan (P.O.P.)

Boston Acoustics® now offers you the opportunity to match your environment with interchangeable grilles for your Boston speakers.



Deep Channel® Design (DCD)
Reduced Baffle Diffraction Design
MagnaGuard® video shielding
Built-in wall mount brackets

bostonacoustics.com/POP

Specifications	HS 40	HS 50	HS 60	HS 225
Frequency Range:	86 Hz – 25 kHz	65 Hz – 25 kHz	56 Hz – 25 kHz	80 Hz – 25 kHz
Recommended Amplifier:	10 – 100 watts	10 – 125 watts	10 – 150 watts	15 – 175 watts
Sensitivity:	89 dB [2.8v at 1m]	89 dB [2.8v at 1m]	89 dB [2.8v at 1m]	89 dB [2.8v at 1m]
Nominal Impedance:	8 ohms	8 ohms	8 ohms	8 ohms
Crossover Frequency:	2,400Hz	2,400Hz	2,400Hz	2,400Hz
Woofers:	4½" (114 mm) DCD with Phase Plugs and MagnaGuard®	5¼" (133 mm) DCD with Phase Plugs and MagnaGuard®	6½" (165 mm) DCD with Phase Plugs and MagnaGuard®	Dual 5¼" (133 mm) DCD with Phase Plugs and MagnaGuard®
Tweeters:	1" (25 mm) Kortec® Soft Dome	1" (25 mm) Kortec® Soft Dome	1" (25 mm) Kortec® Soft Dome	1" (25 mm) Kortec® Soft Dome
Dimensions (H x W x D):	8⅞ x 6½ x 5⅝" (224 x 164 x 151 mm)	11⅞ x 8⅞ x 7⅞" (281 x 205 x 187 mm)	13⅞ x 10 x 9⅞" (347 x 254 x 230 mm)	6⅝ x 19¼ x 6¾" (174 x 488 x 170 mm)



Boston Acoustics® UK · Kingsbridge House · Padbury Oaks, 581 Bath Road · Longford Middlesex · UB7 0EW
Phone: +44 (0) 1753 287947 · E-Mail: orders@bostona-europe.com · support@bostona-europe.com
www.bostonacoustics.com